

Optoma H30

DDR Digital Light Processingtm Projector

- Advanced Double Data Rate DLPtm Technology from **Texas Instruments**
- Fully HDTV compatible with 720p, 1080i
- ✤ 800 lumens and 2000:1 contrast for superior color reproduction
- * Pixelworks scaler and deinterlacer for optimal video processing
- Economy mode extends lamp life and minimizes noise
- * Four-speed, six-segment color wheel
- Adjustable color matrix allows for reds, greens and blues to be independently controlled





Specifications

Display Type:

0.55-inch 12-degree DDR DLPtm technology from Texas Instruments

Resolution:

800 x 600 SVGA (native) 800 x 480 in widescreen

Brightness: 800 Lumens (typical)

Contrast Ratio: 2000:1 (Full On/Full Off)

Lamp Type and Life: 180-watt P-VIP lamp 2,000 (standard) to 3,000 hours

(economy)

Throw Ratio: (Distance/Width) 1.75:1 – 2.12:1

Aspect Ratio: 1.78:1 at 850 x 480 1.33:1 at 800 x 600

Image Size (diagonal): 29 to 260 inches

Projection Distance: 4.1 to 32.8 feet

Compatibility:

SVGA, VGA, SXGA compression VESA, Macintosh, Full

HDTV:

720p, 1080i, SDTV (480i), EDTV (480p), 576i/p

Projection Lens: F/ 2.4 to 2.7. f =19.7 to 23.6 mm Manual focus and zoom

Refresh Rates:

15.75 to 68.70 kHz Horizontal 43 to 85 Hz Vertical

Dimensions (W x H x D): 10.7 x 3.4 x 8.3 inches (271 x 87 x 212 mm)

Weight: 4.6 pounds (2.1 kg)

Noise Level: 32 dB standard (30 dB economy)

User Controls: Onscreen Menu Adjustments Supports Ten Languages

Power Supply: 100-240 volts, 180 watts, 50/60 Hz

Power Consumption: 270 watts (max), standby <5 watts

I/O Connectors:

VGA input (analog RBG/ component/HDTV), S-Video, composite video (RCA), VGA output for monitor loop through

Temperature:

Operating Temperature 41° – 95°F (5° – 35°C) Humidity 80% maximum Storage Temperature -4° - 140°F (-20° - 60°C) Humidity 80% maximum

Standard Accessories:

Extended Warranty, Gold Service, Ceiling Mount Kit, VGA to HDTV/Component Cable, S-Video Signal Cable, Composite Video Cable, USB Cable

Optional Accessory: Ceiling Mount Kit

Competitive Warranty: Two years, 90-days on lamps

NTSC/PAL/SECAM